



Half Value Layer Attenuator Set

GAMMEX 115A

Determining the Half Value Layer (HVL) of the x-ray beam is the standard method

for specifying the quality of the x-ray beam. For a given kVp, a measurement of the HVL gives information on the total filtration in the x-ray beam. Too little filtration results in unnecessary radiation to the patient and too high of a HVL may require increased kVp and mAs, increasing tube loading and reducing tube life.

Gammex 115A Half Value Layer Attenuator Set contains nine sheets of 1100 Aluminum Alloy ranging in thicknesses from 0.1 to 2.0 mm. For your convenience these

sheets come in a plastic storage case to help maintain flatness and for ease of storage and transportation.

SPECIFICATIONS

Construction 1100 Aluminum Alloy (99.0% Pure)

Size. 10x10 cm (4x4 in)

Weight. 0.2 kg (0.4 lbs)

Nine Individual Aluminum Sheets

Thickness

(1) 2.0 mm

(2) 1.0 mm

(2) 0.5 mm

(1) 0.2 mm

(3) 0.1 mm





GAMMEX 115A

DIAGNOSTIC RADIOLOGY



0608 © Gammex, Inc. All rights reserved.

GAMMEX INC.
P.O. BOX 620327
MIDDLETON, WI 53562-0327
USA
+1 800 GAMMEX1 (426 6391)
+1 608 828 7000
FAX: +1 608 828 7500
EMAIL: SALES@GAMMEX.COM

GAMMEX-RMI LTD.
BROADWAY BUSINESS CENTRE
32A STONEY STREET
NOTTINGHAM NG1 1LL
UNITED KINGDOM
+44 (0) 115 924 7188
FAX: +44 (0) 115 924 7189
EMAIL: UKSALES@GAMMEX.COM

GAMMEX-RMI GMBH
FRANKFURTER STRASSE 15
D-35390 GIESSEN
GERMANY
+49 (0) 641 250 9176
FAX: +49 (0) 641 966 2642
EMAIL: DESALES@GAMMEX.COM

For more information contact GAMMEX today at 1 800 GAMMEX 1 (426 6391) or visit WWW.GAMMEX.COM